



1213

DECLARATION OF PERFORMANCE**No: DoP-DD-60H-01-EN****Unique identification code of the product-type:**

DiaDrain-60H

Intended use:

Flow-delay retention board for intensive green roofs, made of recycled high-impact polystyrene (HIPS). As per standard:

EN 13252:2016

function: D

Manufacturer:

APP Kft.
H-9028 Győr
Fehérvári út 75.

Tel.: +36 96 / 512 910
Fax: +36 96 / 512 914
info@diadem.com
www.diadem.com

APP Dachgarten GmbH
Jurastrasse 21
D-85049 Ingolstadt

Tel.: +49 841 / 370 9496
Fax: +49 841 / 370 9498
info@grundach.com
www.grundach.com

System of AVCP: 2+**Harmonised standard:** EN 13252:2016**Notified body:** SKZ-Testing GmbH**Certificate number:** 1213-CPR-6574**Declared performance:**

Essential characteristics	Unit	Performance	Tolerance	Harmonised technical specification
Water flow capacity (rigid/soft, MD, 20kPa, i=1)	l/(ms)	16	-3	EN ISO 12958
Tensile strength MD	kN/m	NPD	NPD	EN ISO 10319
Tensile strength CMD	kN/m	NPD	NPD	
Elongation MD	%	NPD	NPD	
Elongation CMD	%	NPD	NPD	
Durability	Has to be covered in 1 day after installation. Predicted to be durable for a minimum 5 years in natural soils with 4<pH<9 and soil temperatures <25°C			EN 13252

The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Zoltan Magyar, Head of Technology, Product Development

Date: 12.01.2018. Győr, Hungary

Signature